

SPECIFICATIONS

Page 1 of 1
Tri-Cities Work Release
Vinyl Flooring

ITEM NO.	DESCRIPTION	CHECK IF AS SPECIFIED	DESCRIBE FULLY IF NOT AS SPECIFIED
1	Remove / Tear out and dispose existing old floor covering Furnish and install new Vinyl flooring		
	Same Vinyl product used throughout 3 rooms Mannington BioSpec or equal / better BioSpec homogeneous sheet flooring features solid vinyl composition and through-chip construction. Even under the heaviest rolling loads and highest traffic, it won't split, crack or delaminate. Color is Taupestone or similar, final selection of color at time of order.		
	Size of rooms: 7' 3" X 7' 3" – RESTROOM 28' 5" X 13' 6" - VISITING ROOM 32' 6" X 31' - DINNING ROOM / MULTI-PURPOSE AREA		
	Installation will be performed by an authorized / trained technician.		
	Gauge: Overall Nominal Thickness -- .080" (2.03mm) Load Limit: Static Load Limit -- 125 p.s.i. (8.80 kg/cm ²) Reference Specifications: ASTM F-1303-97 -- Type II, Grade 1, Backing Class N/A Traffic: Moderate to Extra Heavy		
	Warranty: BioSpec Limited 5-Year Commercial Warranty		
	<u>Tool Inventory</u> All vendors on site will have to have a quick briefing on Security issues. Vendors must submit an inventory of all tools that will be on the job site.		
	<u>Mandatory Pre-Bid Visit</u> <u>All Bidders Must ATTEND</u> Location: Dept. of Corrections, 524 E. Bruneau Ave., Kennewick, WA 99336 Contact Name: Debra Prichard @ (509) 585-2201 Date: January 11 th , 2010 @ 10:30 am		